



This guide provides installation instructions for the Stand Alone WebClient.

The stand alone WebClient can be used with any IMAP server as long as the server is defined in the host file. Below are instructions for adding the content needed to the host file.

Before the installation, make sure that you have Apache and PHP installed. You will need the additional services for Virus checking and Spam control within the MTA and your IMAP server. This stand alone WebClient will use the server's LDAP directory for username/password information.

The IMAP and SMTP services will be used on the server once the entries for the host file have been added.

Step 1: Run the install script downloaded from the link below:

<https://beyond.bynari.net/files/server/insight-webclient-5.0-i386.sh>

Step 2: Run change mode on the file once it is loaded onto the system.

```
# chmod +x insight-webclient-5.0-i386.sh
```

Step 3: Then run the command –

```
# ./insight-webclient-5.0-i386.sh
```

Step 4: Configure the host file within the WebClient service

Example host file:

```
# echo 192.168.30.31 mail.example.net mail>> /opt/insight/etc/hosts
```

(Make sure the domain name is correct, but leave the “mail” in place. The important part here is the IP address)

Then restart services:

```
# insight restart
```

This will update the internal host file and also restart the service. You will then be able to log into the WebClient and start using the service.

For additional questions or assistance, contact the support team: support@bynari.net



4/25/07

Bynari Inc.
[6220 Gaston Ave. Suite 403, Dallas, Tx 75214](http://6220.Gaston.Ave.Suite.403.Dallas.Tx.75214)
www.bynari.net

Copyright 2007